

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : WA NF742/NF743 Canister Adhesive

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive for laminate

1.3. Details of the supplier of the safety data sheet

Wilsonart LLC

P.O. Box 6110

Temple, TX 76503

Information phone: 800-433-3222 (USA)

In Case of Emergency Contact CHEMTREC (International): 703-527-3887

1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Press. Gas (Liq.) H280

Skin Sens. 1 H317

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated
H317 - May cause an allergic skin reaction

Precautionary statements (GHS-US) :

P261 - Avoid breathing mist, spray, vapors
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap and water
P321 - Specific treatment (see first aid instructions on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
trans-1,2-Dichloroethylene	(CAS No) 156-60-5	40 - 70*
(E)-1-Chloro-3,3,3-trifluoroprop-1-ene	(CAS No) 102687-65-0	7 - 13*
Modified Rosin Ester	Proprietary	1 - 5*

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause an allergic skin reaction.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : May cause skin irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : May cause gastrointestinal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.
- Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Pressurized container: may burst if heated.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

6.4. Reference to other sections

See Sections 8 and 13.

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Closed containers may explode if exposed to extreme heat. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Ground/bond container and receiving equipment. Prohibit smoking in storage area. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

trans-1,2-Dichloroethylene (156-60-5)	
ACGIH TWA (ppm)	200 ppm
Remark (OSHA)	OELs not established
(E)-1-Chloro-3,3,3-trifluoroprop-1-ene (102687-65-0)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Eye protection. Gloves.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Rubber or Neoprene Gloves.

Eye protection : Wear eye protection, including chemical splash goggles and face shield when the possibility exists for eye contact due to spray mist or airborne particles.

Skin and body protection : Wear long sleeves. If process results in dust, mist, or airborne particles consider wearing chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : If inadequate ventilation recommend wearing a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid.

Appearance : Liquid adhesive in pressurized canister.

Color : Green or natural

Odor : Characteristic.

Odor Threshold : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Product is nonflammable, but heat sources may burst canister (chemical under pressure).

10.5. Incompatible materials

Copper and copper alloys, strong acids, alkalies and oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Various hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

trans-1,2-Dichloroethylene (156-60-5)	
ATE CLP (gases)	4500 ppmV/4h
ATE CLP (vapors)	11 mg/l/4h
ATE CLP (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Product may kill grasses and small plants. Not expected to be toxic to fish. Moderately toxic to amphibians. May cause gastrointestinal distress to birds and mammals through ingestion.

12.2. Persistence and degradability

WA NF742/NF743 Canister Adhesive

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3500, Chemical under pressure, n.o.s. (trans-1,2-Dichloroethylene and (E)-1-Chloro-3,3,3-trifluoroprop-1-ene, 2.2

UN-No.(DOT) : 3500

DOT NA no. : UN3500

Proper Shipping Name (DOT) : Chemical under pressure, n.o.s.
trans-1,2-Dichloroethylene and (E)-1-Chloro-3,3,3-trifluoroprop-1-ene

Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg
CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

WA NF742/NF743 Canister Adhesive

All components of this product are listed on the TSCA Inventory or are exempt

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WA NF742/NF743 Canister Adhesive

SARA Section 311/312 Hazard Classes

Health hazard - Respiratory or skin sensitization
Physical hazard - Gas under pressure

15.2. International regulations

No additional information available.

15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54 µg/day

trans-1,2-Dichloroethylene (156-60-5)

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Talc (14807-96-6)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

2,6-Di-tert-butyl-p-cresol (128-37-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Ethylbenzene (100-41-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List


Dipropylene glycol monomethyl ether (34590-94-8)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : New SDS Created.
Revision date : 11/28/2017
Other information : Author: MDT

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS III Rating

Health : 2*
Flammability : 1
Physical : 0

WA NF742/NF743 Canister Adhesive

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protection

:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product