

**Safety Data Sheet**

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/15/2016

Supersedes: 12/10/2013

SDS # 19866

Version: 6

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Wilsonart 740/741 Adhesive

Product form : Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Adhesive for laminate

**1.3. Details of the supplier of the safety data sheet**

Wilsonart LLC

P.O. Box 6110

Temple, TX 76503-6110

Information phone: 800-433-3222 (USA)

In Case of Emergency Contact CHEMTREC (International): 703-527-3887

**1.4. Emergency telephone number**

Emergency number : CHEMTREC: (800) 424-9300

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GHS-US classification**

Compressed gas H280

Flam. Liq. 1 H224

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

Asp. Tox. 1 H304

**2.2. Label elements****GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS02



GHS04



GHS07



GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H224 - Extremely flammable liquid and vapor  
H280 - Contains gas under pressure; may explode if heated  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe gas  
P264 - Wash clothing, hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection, face protection, protective clothing, protective gloves  
P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see first aid instructions on this label)  
P331 - Do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use foam, dry extinguishing powder, carbon dioxide (CO<sub>2</sub>), Water fog to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Acetone	(CAS No) 67-64-1	10 - 30*
Petroleum gases, liquefied, sweetened	(CAS No) 68476-86-8	10 - 30*
Propane	(CAS No) 74-98-6	7 - 13*
Isobutane	(CAS No) 75-28-5	7 - 13*
Dimethyl ether	(CAS No) 115-10-6	5 - 10*
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	1 - 5*
Cyclohexane	(CAS No) 110-82-7	1 - 5*
Pentane	(CAS No) 109-66-0	1 - 5*
Isopentane	(CAS No) 78-78-4	1 - 5*
Toluene	(CAS No) 108-88-3	1 - 5*
Hexane	(CAS No) 110-54-3	0.1 - 1*
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	0.1 - 1*

\*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause drowsiness or dizziness. Causes serious eye irritation. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May displace oxygen and cause rapid suffocation. May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. . May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water fog.

Unsuitable extinguishing media : Direct water spray.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable liquid and vapor.

Explosion hazard : Static discharge may serve as an ignition source for this product. Pressurized container: may burst if heated.

Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : vapors may travel long distances along ground before igniting/flashing back to vapor source. This material is flammable and may be ignited by heat, sparks, or static electricity.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

#### 6.4. Reference to other sections

See Sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Ground/bond container and receiving equipment. Prohibit smoking in storage area. Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Cyclohexane (110-82-7)</b>	
ACGIH TWA (ppm)	100 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	300 ppm
<b>Isopentane (78-78-4)</b>	
ACGIH TWA (ppm)	600 ppm (listed under Pentane, all isomers)
Remark (OSHA)	OELs not established
<b>Pentane (109-66-0)</b>	
ACGIH TWA (ppm)	600 ppm (listed under Pentane, all isomers)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	2950 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	1000 ppm
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Hexane (110-54-3)</b>	
ACGIH TWA (ppm)	50 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	500 ppm
<b>Toluene (108-88-3)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;
<b>Petroleum gases, liquefied, sweetened (68476-86-8)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Isobutane (75-28-5)</b>	
ACGIH STEL (ppm)	1000 ppm
Remark (OSHA)	OELs not established
<b>Propane (74-98-6)</b>	
ACGIH TWA (ppm)	1000 ppm (listed under Aliphatic hydrocarbon gases: Alkane C1-4)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	1000 ppm
DNEL	>=
<b>Dimethyl ether (115-10-6)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Acetone (67-64-1)</b>	
ACGIH TWA (ppm)	500 ppm
ACGIH STEL (ppm)	750 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	1000 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup> (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)
OSHA PEL (STEL) (ppm)	1000 ppm

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Personal protective equipment

: Protective goggles. Gloves. Wear chemically impervious apron over labcoat and full coverage clothing. Insufficient ventilation: wear respiratory protection.



### Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Rubber or Neoprene Gloves.

### Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

### Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

### Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid adhesive in pressurized canister.
Color	: No data available
Odor	: Solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -104 °C Open Cup (-156 °F)
Auto-ignition temperature	: 225 °C (n-Hexane 437 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: Greater than air
Relative density	: 0.67 - 0.69
Solubility	: Insoluble.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 1.1 - 27 vol % (1.1% for n-Hexane and Toluene, 27% for Dimethyl Ether)

### 9.2. Other information

VOC content	: 490 g/l
-------------	-----------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Heat, flame. Ignition sources.

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

Copper and copper alloys, strong acids, alkalies and oxidizers.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Various hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Cyclohexane (110-82-7)	
LD50 oral rat	12705 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	13.9 mg/l/4h

Isopentane (78-78-4)	
LC50 inhalation rat (mg/l)	280000 mg/m <sup>3</sup> 4 h

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	364 g/m <sup>3</sup> 4 h

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h

Hexane (110-54-3)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Isobutane (75-28-5)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
ATE CLP (vapors)	658.000 mg/l/4h
ATE CLP (dust, mist)	658.000 mg/l/4h

Propane (74-98-6)	
LC50 inhalation rat (mg/l)	658 mg/l/4h
ATE CLP (vapors)	658.000 mg/l/4h
ATE CLP (dust, mist)	658.000 mg/l/4h

Dimethyl ether (115-10-6)	
LC50 inhalation rat (mg/l)	308.5 mg/l/4h (Source: IUCLID)

Acetone (67-64-1)	
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup>

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. . May cause damage to organs through prolonged or repeated exposure.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Product may kill grasses and small plants. Not expected to be toxic to fish. Moderately toxic to amphibians. May cause gastrointestinal distress to birds and mammals through ingestion.

#### 12.2. Persistence and degradability

##### Wilsonart 740/741

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN3501 Chemical under pressure, flammable, n.o.s. (Isobutane, Propane, Dimethyl Ether), 2.1
UN-No.(DOT)	: 3501
DOT NA no.	: UN3501
Proper Shipping Name (DOT)	: Chemical under pressure, flammable, n.o.s. (Isobutane, Propane, Dimethyl ether)
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas



DOT Quantity Limitations Passenger aircraft/rail : Forbidden  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 75 kg  
CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

#### Additional information

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Wilsonart 740/741

All components of this product are listed on the TSCA Inventory or are exempt
---

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Wilsonart 740/741</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
<b>Cyclohexane (110-82-7)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313
<b>Acetone (67-64-1)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Not Listed on US SARA Section 313
<b>Isopentane (78-78-4)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	
Section 313	Not listed on US SARA Section 313
<b>Pentane (109-66-0)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	
Section 313	Not listed on US SARA Section 313
<b>Toluene (108-88-3)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313
<b>n – Hexane (110-54-3)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Not Listed on US SARA Section 313
<b>Isobutane (75-28-5)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	
Section 313	Not listed on US SARA Section 313
<b>Propane (74-98-6)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	
Section 313	Not listed on US SARA Section 313
<b>Dimethyl ether (115-10-6)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	
Section 313	Not listed on US SARA Section 313



# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	7000 µg/day

Benzene (71-43-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	Yes	No	Yes	6.4 µg/day

Cyclohexane (110-82-7)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				

Isopentane (78-78-4)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Pentane (109-66-0)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Hexane (110-54-3)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Toluene (108-88-3)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				

Isobutane (75-28-5)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Propane (74-98-6)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Dimethyl ether (115-10-6)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Acetone (67-64-1)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Benzene (71-43-2)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				

# Wilsonart 740/741

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information


Indication of changes : Revision 5  
: 07/15/2016

Other information : Author: MDT.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



#### HMIS III Rating

Health : 2\*

Flammability : 4

Physical : 0

Personal protection :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product