

**COLOR MATCHED  
CAULK**

# COLOR MATCHED CAULK

## FOR KITCHENS, BATHROOM & LAMINATE



### General Description

- Wilsonart® Color Matched Caulk is a 100% siliconized acrylic that is formulated to color match Wilsonart® Laminate and other high pressure countertops, floors, casework, sinks, tubs and showers.
- Stain, mold and mildew resistant
- Stays flexible
- Easy water clean-up
- Water-resistant
- Consumer or professional use
- Does NOT contain Etylene Glycol

### Availability

- 5.5-ounce squeeze tube (6-pack)
- 10.5-ounce cartridges (6-pack)

### Storage/Shelf Life

- DO NOT ALLOW PRODUCT TO FREEZE.
- Close container tightly when not in use and store off the floor in a well ventilated area.
- Rotate stock.
- Shelf life expires 18 months from manufacture date.

### Surface Preparation

Surface must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint and old caulking. Apply only when caulk, air and substrate temperatures are above 50°F. Thoroughly rinse surface and allow to dry completely before caulking and painting.

### Directions

1. Clip off tip of spout at a 45° angle to desired size.
2. Apply using steady, even pressure to completely bridge joints.
3. Smooth caulk using wet finger for a neat appearance.
4. Wipe away excess with a damp cloth before surface skins over.
5. Protect from water until cured (72 hours). May be painted over in 4-6 hours depending on climatic conditions. Larger beads may require longer drying time. Cool, humid conditions will prolong drying time.

### For Best Results

- Apply caulk in temperatures between 50°F and 90°F.
- Store caulk at temperatures between 50°F and 90°F.
- Do not use for constant water exposure applications.
- Do not use for joints subject to heavy abrasion or wear.
- Do not attempt to thin caulk
- For a neat, straight bead edge, mask both sides of joint with masking tape.
- Do not "overtool" the applied caulk, leaving too little caulk to perform, following cure.

### Clean-up

Clean skin and equipment immediately after use with warm water and a mild soap.

### Physical Properties

Vapor Density (Air=1):	> 1
Solubility in Water:	Soluble
Appearance:	Smooth, viscous paste
Odor:	Mild acrylic odor
Specify Gravity (H2O =1):	~ 1.60 -1.56
Percent Volatiles by weight (%):	~ 16 -18
pH:	~ 7.0 - 7.5
Total Non-Volatile % Solids (Weight):	82% (Computrac Analyzer)
Flexibility:	Conforms to ASTM 734
Tack Free Time:	< 1 hr @ 77°F (ASTM D-2377)
Shelf Life:	18 months

### Volatile Organic Compounds (VOC):

The use, supply, sale or offer for sale of this product in certain states and localities may be prohibited if it exceeds certain VOC limits. Please check state and local regulations for any prohibitions on the sale and use of this product

### Clean-up

Clean skin and equipment immediately after use with warm water and a mild soa

### Warranty

**NO WARRANTY:** WILSONART MAKES NO WARRANTIES, EXPRESS OR IMPLIED. NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. The person using the product (the "User") is solely responsible for determining whether the Wilsonart product is appropriate and/or suitable for User's purpose and method of application.

**LIMITATION AND EXCLUSION OF REMEDIES AND DAMAGES:** The exclusive and sole remedy, and Wilsonart's exclusive and sole obligation, for any defect of this Wilsonart product is the refund of the purchase price of the product. Wilsonart shall not, under any circumstances or under any legal theory, be liable to the Purchaser or any other person for special, incidental or consequential damages of any nature, including without limitation damages to, or loss of use of, property, damages for loss of profits or revenues or any other damages arising from the purchase or use of the product. Wilsonart's liability will in no event exceed the purchase price of the product.

### Precautionary Information

Refer to product label and material safety data sheet for Health & Safety information before using this product.

### Contact

Customer Service: 1-800-433-3222 or adhesives@wilsonart.com  
Visit [www.wilsonartadhesives.com](http://www.wilsonartadhesives.com) for information