

131

ADHESIVE CLEANER

OTC COMPLIANT FOR REMOVING RESIDUE & OVERSPRAY

General Description

- A blend of light hydrotreated distillate, acetone, isopropyl alcohol that is designed to dissolve and remove dried adhesive overspray and residue from fabricated parts and decorative surfaces
- An Ozone Transparent Commission (OTC) compliant cleaner that removes overspray and adhesive residue from fabricated parts and decorative surfaces by only dissolving the adhesive resins and not the rubber
- This product does not require stirring before use
- For professional or consumer use
- Effective by only dissolving the adhesive resins and not the rubber
- No smearing or leftover adhesive film after drying

Applications to avoid

- Do not use this product to clean equipment (spray guns, fluid lines, hoses, spray pots, rollers, brushes, etc.).
- Do not use this product or any other to thin Wilsonart Adhesives.

Availability

1-gallon cans, 5-gallon pails, 55-gallon drums

General Use Instructions

Use only after you have read and understand the warnings, safety measures and first aid instructions printed on container. Apply and allow to dry only in a well ventilated area. Use outdoors when possible. If indoors, open all windows and doors, and shut off all sources of ignition.

For Adhesive Residue Removal

Dab rag in cleaner and lightly rub residue, increasing rubbing pressure as needed. Keep rag wet with cleaner for best results.

Storage/Shelf Life

- Close container tightly when not in use.
- Rotate stock.
- Shelf life expires 2 years from manufacture date.
- Store in a cool, well ventilated area and away from ignition sources.

Clean-up/Disposal

Dispose of waste cleaner and cleaner soaked rags in accordance with regulations. Empty container may contain hazardous residue or flammable vapors which may explode upon ignition. Do not allow in any sewers, on the ground or into any body of water. Contact local authorities for further guidance.

Primary Contents

Light hydrotreated distillate (CAS# 68410-97-9), Acetone (CAS# 67-64-1), Isopropyl Alcohol (CAS# 67-63-0)

Shipping Information

- Ship Domestic Ground
- UN1993 Flammable Liquid, N.O.S. (Contains Acetone, Isopropyl Alcohol), Class 3, PGII

Precautionary Information

Refer to product label and material safety data sheet for Health & Safety information before using this product.

Physical Properties

Color:	Clear
Odor:	Strong Solvent
Density:	6.53 lbs/gallon
Solids Content:	0%
VOC/liter of material:	154 g/L (Calculated)
VOC(less water & exempt solvents):	759 g/L (Calculated)
VHAP Content:	0 g/l (0.00 lbs/gal)
Flashpoint:	-18.9°C/-2°F (Closed Cup)
Composite part. pres.:	5.4 mm Hg @20°C (Calculated)
Nonphotochemically Reactive	

Warranty

NO WARRANTY: WILSONART MAKES NO WARRANTIES, EXPRESS OR IMPLIED. NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. The person using the product (the "User") is solely responsible for determining whether the Wilsonart product is appropriate and/or suitable for User's purpose and method of application.

LIMITATION AND EXCLUSION OF REMEDIES AND DAMAGES: The exclusive and sole remedy, and Wilsonart's exclusive and sole obligation, for any defect of this Wilsonart product is the refund of the purchase price of the product. Wilsonart shall not, under any circumstances or under any legal theory, be liable to the Purchaser or any other person for special, incidental or consequential damages of any nature, including without limitation damages to, or loss of use of, property, damages for loss of profits or revenues or any other damages arising from the purchase or use of the product. Wilsonart's liability will in no event exceed the purchase price of the product.

Contact

Customer Service: 1-800-433-3222 or adhesives@wilsonart.com
Visit www.wilsonartadhesives.com for information